



## Technical Specifications

### Space Requirements

**Product Line Opening:** Required 3" diameter hole in countertop for product lines when unit set up with support feet shown.

**Countertop Minimum Depth:** 24" (with 3.95" overhang at front of counter). For no overhang, 28" countertop depth is required.

**Height Clearance:** Minimum 37" height space from top of countertop for machine, such as cabinetry.

### Electrical Requirements

110-120 VAC / 60Hz / 9A max current draw  
GFCI protected, 3-prong outlet

### Weight

Shipping Weight: 121 lbs (54.9kg)  
In-Use Weight: 180 lbs (81.65kg)

### Unit Dimensions

29.9" x 13.3" x 27.95" (HxWxD)

### Plumbing

Dedicated 3/8" plumbing line with shutoff, rated for a maximum of 145psi. Minimum supply pressure of 50psi and 1.3 gal/min (5 liters/minute) flow rate.

Inline filtration system recommended for install between water main and dispenser.

The internal ice bank requires a drain line or an external overflow container

### CO<sub>2</sub> Tank

Minimum 10lb CO<sub>2</sub> tank required for machine use.

### Internet Access

Ethernet or wireless internet connection required to access smart functions of the JuLi. Secure restricted access to technical menu by authorized personnel only.

### Contact Us

[www.smartsoda.com/contact-us](http://www.smartsoda.com/contact-us)  
+1 (888) 998-9668.